



NEW

PFT SAMBA L

Airless-spraying technology for professional applicators for all painting works

Functional description

PFT SAMBAL can be used for almost all construction paints. Its application field includes home painting works up to big professional construction sites – interior and exterior. It unites flexibility, perfection in processing and easy handling due to its exclusive industrial technology. Every construction site can be finished time saving in comparison to the traditional application with paintbrush and roll.

Fields of application

It can be used for almost all painting works like:

- ▶ Acrylic paints water-based
- ▶ Acrylic paints solvent-activated
- ▶ Interior / exterior dispersion paints
- ▶ Mesh adhesives
- ▶ Silicate paints
- ▶ Latex paints and emulsions

Advantages at a glance

- ▶ robust and height-adjustable chassis chrome-plated, stainless and corrosion-protected
- ▶ hose holder integrated
- ▶ easy cleaning and maintenance without tools
- ▶ brushless geared motor 230 V, 1 phase
- ▶ self-priming pump
- ▶ big pneumatic tires for comfortable transport
- ▶ compact construction design, faster pressure increase for high capacity
- ▶ best price and condition



All rights and technical changes reserved. We provide guarantee as far as faultless and proper finishing of our machines is concerned. Figures given in relation to output, equipment and performance are based on experience and can vary in case of changing circumstances. Furthermore, the instructions of the material/mortar manufacturers must be observed. Alterations, reprints and photomechanical reproductions, even in extracts, require the permission of Knauf PFT GmbH & Co. KG.

PFT SAMBA L-GB/1M/05.09/ROT



Knauf PFT

Technical Hotline:

▶ +49 9323 31-1818

▶ Phone +49 9323 31-760

▶ Fax +49 9323 31-770

▶ info@pft-iphofen.de

▶ www.pft.eu

Technical data

Part no.	00 12 47 09
Conveying capacity	max. 3.0l/min
Conveying pressure	max. 200 bar
Size of the nozzle	max. 0.027"
Drive	1.3 kW

Dimensions

Total length	approx. 650 mm
Total width	approx. 560 mm
Total height	approx. 730–980 mm adjustable in height

Weights

Total weight	approx. 39 kg
---------------------	---------------

PFT SAMBA L

Basic equipment

Spraying gun complete with
 – color pistol
 – high pressure hose 15 m
 – cleaning and service fluid
 – operating instructions

Knauf PFT GmbH & Co. KG
 P.O. Box 60
 97343 Iphofen
 Einersheimer Straße 53
 97346 Iphofen
 Germany

Knauf Gips KG
 Dry construction-, Gypsum plaster-
 and Soil-Systems

Knauf AMF GmbH & Co. KG
 Ceiling Systems

Knauf Integral KG
 Gypsum Fibre Material

Knauf Marmorit GmbH
 Mineral Facade Systems

Knauf Dämmstoffe GmbH
 Polystyrene Insulating
 Material

Knauf Insulation GmbH
 Glasswool-Isolation, XPS

Knauf Perlite GmbH
 aquapanel® CementBoards,
 Perlit